





## Pure racing performance. All-new 2019 TVS Apache RTR 180 (BS IV) with SUPER-MOTO ABS



### TVS APACHE RTR 180 ABS SPECIFICATIONS>

#### ENGINE

Type Displacement Maximum Power

Maximum Torque Bore x Stroke No. of cylinders Compression Ratio Carburetor Valve Train Valves per Cylinder Startina Idle Speed lanition Power-to-Weight Ratio

### 12.22kW @ 8500rpm (as per IS 10000 part IV) 15.5±0.3Nm @ 6500±200rpm 62.5mm x 57.8mm 9.5±0.5:1

SI, 4 Stroke, Air cooled

UCAL BS-29 2 Valves, single overhead cam 2 Valves Electric & Kick Start 1450±200 rpm IDI-Dual mode digital ignition

> Metallic 12±0.5

## **RTR OVERSQUARE** ENGINE

**RACE PROVEN** 

PERFORMANCE

The racing short stroke/low-end torque engine has the best-in-class power-to-weight ratio & produces 12.22kW @8500 rpm (16.62PS @8500 rpm)

## SUPER-MOTO ABS

Developed and tested on the track, the system provides the ultimate braking control while allowing sharp feedback. The precise system to keep your braking and cornering, razor-sharp.



## MIG SUSPENSION

The race derived monotube inverted gas filled suspension, has 5 step adjustable shocks for perfect riding dynamics.

### SYNCHRO STIFF CHASSIS

Ensures total control at high speeds and tight corners. It provides stiffness for straight line performance and flex for aggressive cornering.





139 kg

130 kg

114 km/h





now more, scan or visit www.tvsapache.com

# **CUTTING-EDGE RACE DESIGN**

## **BEAST-INSPIRED** HEADLAMPS



The LED light guide combined with the pilot lamps form a pair of intense animalistic eyes.

### **SCULPTED DIGITAL** DISPLAY

The nocturnal backlit console has race-inspired carbon fibre cues with a racina stripe desian. The high-tech console features a lap time recorder and top speed indicator.

### MUSCLED TANK

The chiselled tank comes with all-new race graphics, inspired by racing lines. The aerodynamic design channels air to reduce engine heat by 10°C.

### **ALCANTARA-LIKE RACING SEAT**

The seat keeps the rider comfortable over long race distances.



#### TVS MOTOR COMPANY TVS

TVS Motor Company Limited, P.B. No. 4, Harita, Hosur - 635 109, Tamil Nadu, India. Telephone: +91 (4344) 276878 / 277311

( 🖸

\*

**#TVSApacheSeries** (D) (f) ( 🎔



Above specifications are certified as per BS IV vehicle norms. \*Headlamp comes with AHO only.

177.4 cm<sup>3</sup>

87.9 kW per 1000kg

Telescopic with Hydraulic Dampers 105 mm Stroke Monotube Inverted Gas-filled shox (MIG) with spring aid

DIMENSIONS Height

**FUEL TANK** 

Capacity (I)

SUSPENSION

Material

Front:

Rear:

Length Width Wheelbase Ground Clearance Saddle Height

### ELECTRICALS

Batterv \*Headlamp Tail Lamp

CHASSIS

Type

12V, 9.0Ah/6 Ah 35/35W Halogen HS1 with MFR Clear lens with Multi Face Reflector 0.5W LED-Twin triangle with prism on lens

Double Cradle SynchroSTIFF

90/90-17 49P Tubeless

110/80-17 57P Tubeless

### WHEELS & TYRES

Tyre (Front) Tyre (Rear) Tyres

### BRAKES

Front Rear ABS Brake Fluid

WEIGHTS

Max. Payload

PERFORMANCE

Max. Speed

Kerb Weight with 90% fuel and tool kit





1105 mm 2085 mm 730 mm 1326 mm 165 mm 790 mm